



** SMALL **

ES 135 T

Capacity tons **13,5**

PRODUCT	CORN	WHEAT & BARLEY	SUNFLOWER	RAPE & SOY	RICE
INOX SCREEN	2,5	2,5	2,5	1,5	1,5
BURNER TEMPERATURE	120°	100/105°	65/70°	75/80°	45°
PRODUCT TEMP.	55/63°	45/48°	40/45°	40/45°	28/35°
PS	0,75	0,78	0,55	0,65	0,58
CAPACITY ON TONS	13,9	14,43	10,18	12,03	10,73
CAPACITY ON MC	18,5	18,5	18,5	18,5	18,5

LOAD TIME	CORN	WHEAT & BARLEY	SUNFLOWER	RAPE & SOY	RICE
	20'	20'	20'	20'	45'
D R Y I N G	1½ h.	1½ h.	1¾ h.	1¾ h.	5 h.
	5 lt /t. n. 6½	4 /4,5 lt /t. n. 7½	5/6 lt /t. n. 7	4/5 lt /t. n. 7	4 lt /t. n. 3¼
	2½ h.	2½ h.			
	10 lt /t. n. 5½	8/9 lt /t. n. 5½			
	3½ h.	3 h.			
	14 lt /t. n. 4½	10/11 lt /t. n. 5¼			
COOLING TIME	1¼ h.	1 h.	1 h.	1 h.	45'
UNLOAD TIME	17'	17'	20'	17'	45'

POWER required for:

Tractor drive PTO hp	60	60	60	60
Electric drive kw	30	30	30	30

Burner	kcal/h	700000
Fan	Diameter	710 mc/h 37000


DIAMETER	mt.	2,5
HEIGHT DURING TRANSPORT	mt.	14,47
HEIGHT OF CYLINDER	A mt.	5,57
OPERATING HEIGHT	B mt.	6,07

ESMA SRL - VIA VEGRI, 36 - MONTEGALDA (VI) ITALIA
 Tel. 0039 0 444 412511 Fax 0039 0 444 413230
www.esma.it skype esmasrl



mailto: info@esma.it

OPERATING HEIGHT with dust	C	mt.	6,07
HEIGHT OF OUTLET CHUTE	D	mt.	4,05
LENGHT	E	mt.	4,93
LENGHT with 2,60mt loading hopper	F	mt.	8,14
LENGHT with loading auger	G	mt.	8,14
HEIGHT with electric outlet auger		mt.	
TANK		lt	385
WHEELS			2
DIAMETER OF LOADIN AUGER		mm	200
DIAMETER OF CENTRAL SCREW CONVEYOR		mm	368



The manufacturing company may vary the data without notice. The data relevant to yields are just an indication. These can change considerably according to the environment conditions (temperature, moisture, etc) and the product characteristics (ripening degree, cleaning, etc.) Important differences are possible among the different varieties of the same product.